

# **SAFETY DATA SHEET**

**Product Name:** *STRONGIRT*®

## **SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION**

Product Type: Article

**Manufacturer's Name**: Strongwell Corporation

400 Commonwealth Avenue

Bristol, VA 24210

**Emergency Telephone No.:** 276-645-8000

**24 Hour Emergency Telephone Numbers** 

Chemtrec (US transportation): (800) 424-9300 Canutec (Canadian Transportation): (613) 996-6666 Poison Control Center (Medical): (877) 800-5553

## **SECTION 2 - HAZARDS IDENTIFICATION**

As manufactured, this product is considered non-hazardous.

**CLASSIFICATION**: This product meets the definition of "article" under 29CFR1910-1200(c): a manufactured item (i) which is formed to a specific shape or design during its manufacture; (ii) which has end function(s) dependent in whole or part upon its shape or design during end use; and (iii) which under normal conditions of use does not release more than very small quantities of hazardous chemicals, and does not pose a physical hazard or health risk. If you do not process this product in a manner that will create sufficient quantities of combustible dust to create a hazard, this SDS may not apply.

#### **GHS LABEL:**



**HAZARD STATEMENT:** Product may form combustible dust and particulate matter during drilling, grinding, cutting, or sanding operations. Refer to NFPA 654 for guidance on prevention of fire and dust explosions.

H317: MAY CAUSE AN ALLERGIC SKIN REACTION

H320: MAY CAUSE EYE IRRITATION

## **PRECAUTIONARY STATEMENTS:**

P261: AVOID BREATHING DUST/FUME/GAS/MIST/VAPORS/SPRAY

P280: WEAR PROTECTIVE GLOVES/PROTECTIVE CLOTHING/ EYE PROTECTION/FACE PROTECTION

## **POTENTIAL ACUTE HEALTH EFFECTS:**

INHALATION: Nuisance dust from machining may cause respiratory tract irritation.

EYES: Nuisance dust from machining may cause eye irritation.



SKIN CONTACT: No effects expected under normal use. Nuisance dust from machining may cause irritation.

INGESTION: Unlikely under normal use.

## **SECTION 3 – COMPOSITION / INFORMATION ON INGREDIENTS**

Fiber reinforced polymer (FRP) products are composed of a mixture of resin, inorganic fillers, pigments, processing additives, and fiberglass reinforcement. During the manufacturing process, the mixture is cured and hardened into a solid, stable material that is non-hazardous when handled properly and in accordance with good industrial hygiene practices.

## **SECTION 4 – FIRST AID MEASURES**

Not expected to present a significant health hazard under normal, anticipated use. Dust particles from processing may cause irritation.

**EYES**: Do not rub eyes. While holding the eyelid(s) open, flush with lukewarm, gently flowing water for 5 minutes or until the particle/dust is removed. Obtain medical attention if needed.

**SKIN**: Wash with soap and water.

**INGESTION**: Ingestion is unlikely with normal use.

**INHALATION**: If exposed to excessive levels of dust, remove to fresh air and get medical attention if cough or other symptoms develop.

## **SECTION 5 - FIRE FIGHTING MEASURES**

**EXTINGUISHING MEDIA**: Dry chemical, carbon dioxide, or foam.

**EXPLOSION HAZARD**: Excessive dust buildup (from cutting, grinding or sanding) has the potential to combust.

**FIRE FIGHTING PROCEDURES**: During a fire, irritating and/or toxic smoke may be generated. Wear full firefighting gear with proper respiratory protection (SCBA).

## **SECTION 6 – ACCIDENTAL RELEASE MEASURES**

#### **ENVIRONMENTAL PRECAUTIONS:**

Avoid dust generation during processing. Dust should not be allowed to accumulate and may form an explosive mixture in excessive concentrations.



## **SECTION 7 – HANDLING AND STORAGE**

**GENERAL PROCEDURES**: Avoid contact with eyes, skin, and clothing. Wear proper gloves when handling.

**HANDLING**: Refer to NFPA 654 for additional guidance on safe handling of combustible dusts.

## **SECTION 8 – EXPOSURE CONTROLS / PERSONAL PROTECTION**

Chemical Component	OSHA PELs (Permissible Exposure Limits for the workplace)	ACGIH TLV's (Threshold Limit Values)
Particulate dust	TWA: 15.0 mg/m3 (total dust)	TWA: 5.0 mg/m3 (inhalable fraction)
Particulate dust	TWA: 5.0 mg/m3 (respirable fraction)	TWA: 1 fiber/cm3 (respirable fraction)

**GENERAL PROTECTIVE MEASURES:** Do not inhale dust.

**EYE/FACE PROTECTION**: Wear safety goggles when processing, cutting, grinding, etc.

**PROTECTIVE CLOTHING**: Wear protective clothing to minimize the potential for skin contact with dust.

Irritation may occur from exposure to dust.

**RESPIRATORY PROTECTION**: If respirable fibers/dust are generated, use HEPA respiratory protection.

Dust may cause irritation of mucus membranes and respiratory tract.

## **SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES**

Physical State: Solid

Odor: Mild, Characteristic Odor

Color: Various

**Solubility in Water**: Insoluble

## **SECTION 10 – STABILITY AND REACTIVITY**

**Stable**: Yes, under normal operations.

**Conditions to Avoid**: Flames with combustible dust.

Hazardous Decomposition Products: May form carbon dioxide, carbon monoxide, and toxic fumes when

burned.



## **SECTION 11 – TOXICOLOGICAL INFORMATION**

No toxicological data is available for this product.

#### **SECTION 12 – ECOLOGICAL INFORMATION**

No ecological data is available for this product.

## **SECTION 13 – DISPOSAL CONSIDERATIONS**

As supplied, this product is not hazardous. Dispose of in industrially approved landfills. Consult federal, state, and local regulations for proper disposal.

## **SECTION 14 – TRANSPORT INFORMATION**

This product is not regulated as dangerous or hazardous goods for shipping.

SHIPPING SYMBOLS/PLACARDS: N/A

## **SECTION 15 – REGULATORY INFORMATION**

**HMIS RATING** 



**NFPA CODES** 



U.S. EPA CERCLA: NA

## SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)

311/312 HAZARD CATEGORY: NA

**RCRA STATUS:** This product, if discarded as a solid, is not a federal RCRA hazardous waste. Processing, use or contamination of this product may change the waste management options. State and local disposal regulations may differ from federal disposal regulations.

CALIFORNIA PROPOSITION 65: Raw materials used during the manufacture of these products contain chemicals listed under the California Safe Drinking Water and Toxic Enforcement Act of 1986 (Prop 65) as either a carcinogen or a reproductive toxicant.



# **SECTION 16 – OTHER INFORMATION**

PREPARED BY: STRONGWELL EHS Department

Date Updated: May 27, 2020

## **DISCLAIMER:**

The information and recommendations set forth in this SDS are believed to be accurate as of the date of the SDS preparation. Strongwell Corporation makes no representation or warranty, direct or indirect, regarding the accuracy or completeness, nor does the company assume any obligations to advise you of any modifications or corrections to this document. Recipients are advised to confirm as they may deem acceptable that the information and recommendations are current and applicable to meet their requirements. Since the conditions and methods of use of this product are beyond our control, Strongwell Corporation disclaims any and all liability arising out of the use of this product or the information provided herewith.